


NVR

# 16/32 CH NVR

8MP/5MP/4MP/3MP/1080P/720P HD NVR



## TD-3300H2-A1

- 4K Output
- 8MP
- DDNS
- Network
- PTZ
- Audio
- MIC
- Mobile
- CMS
- USB
- Mouse
- E-mail
- STD
- FR
- VCA

TD-3300H2-A1 series are 16 / 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

TD-3300H2-A1 series support 16 / 32 CH IP input, simultaneous 16 / 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



[en.tvt.net.cn](http://en.tvt.net.cn)

For more information, please visit our website

### Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23<sup>rd</sup> Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: [overseas@tvt.net.cn](mailto:overseas@tvt.net.cn)

### SPECIFICATIONS


Model		TD-3316H2-A1	TD-3332H2-A1	
System	Compression	Standard H.265 / H.264		
	OS	Embedded Linux		
Video	Network Input	16 CH IPC input	32 CH IPC input	
	Network Access Bandwidth	160Mbps	256Mbps	
	Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps		
	Output	HDMI × 1 : 4K × 2K / 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024		
Audio	Network Input	16 CH IPC audio input	32 CH IPC audio input	
	2-way Audio	RCA × 1		
	Local Output	RCA × 1		
Record	Record Stream	Dual stream recording		
	Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P		
	Mode	Manual, timer, motion, sensor		
Playback	Simultaneous Playback	Max 16 CH	Max 16 CH	
	Search	Time slice / time / event / tag search		
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events		
	Function	Play, pause, FF, FB, digital zoom, etc.		
Alarm	Mode	Manual, sensor, motion, exception		
	Input	Support IPC alarm input		
	Output	Support IPC alarm output		
	Triggering	Record, snap, preset, e-mail, etc.		
Face	Channel	16 CH	32 CH	
	Face Picture Database	16 libraries 10000 Face Pictures		
	Computing Capability	240 pictures / minute		
	Face Picture Search	Search by picture is supported		
	Database Management	Add, modify, delete and search face pictures		
	Face Picture Adding	Add face pictures through APP, WEB and local PC		
	External face picture enrollment	Resolution : 64 x 64 ~ 1920 x 1080 Size : less than 200KB Format : jpg		
	Face Picture Comparison	Support allow list and block list alarm		
	Face Trace	Yes		
	Map of Face Trace	Resolution : 600 x 300 ~ 3840 x 2160 Size : within 200KB Format : jpg		
	Statistic Graph of Face Information	Bar graph, pie chart		
	Statistic Mode of Face Information	Statistics by day, week, month, quarter as well as customized time period		
	Network	Interface	RJ45 10 / 100 / 1000 Mbps × 1	
		Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP	
Web Client		Max 10 users online		
Mobile Device	OS	iOS, Andriod		
Storage	HDD	SATA × 2, max 8T per HDD		
Backup	Local Backup	U disk, USB mobile HDD		
	Network Backup	Yes		

Port	USB	USB 2.0 × 1 ( front panel ), USB 3.0 × 1 ( rear panel )
	Remote Controller	Optional
Others	Power Supply	DC 12V
	Consumption	≤ 15W ( without HDD )
	Dimensions (mm)	380 × 268 × 52 ( W × D × H )
	Work Environment	-10 ~ 50 °C , 10% ~ 90% humidity

### Features

- Support 16 / 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event, tag, smart and target database search
- Support face detection and comparison
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

### DIMENSIONS



## Rear Panel

