

Secure The World With You www.tvt.net.cn

32 CH PoE NVR HDMI Display



TD-3232H4-16P

8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P HD PoE NVR



TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 5F, North Block, CE Lighting House, Hi-Tech Park, Nanshan District, Shenzhen City, Guangdong Province, P.R.China 518057

Tel: +86-755-3330 6001 Fax: +86-755-3330 6002

Web site: www.tvt.net.cn E-mail: overseas@tvt.net.cn

8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P **HD PoE NVR**

























MIC

USB

Introduction

TD-3232H4-16P series are 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition PoE NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system. TD-3232H4-16P series integrate with 16 PoE network ports, support 16 CH IPC direct connection to NVR , simultaneous 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.


Characteristics

- Support 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 16 CH simultaneous playback
- Search: time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- 16 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

Specification

| Model | | TD-3232H4-16P |
|------------------|------------------------------|--|
| | Compression | Standard H.265, H.264 |
| System | os | Embedded Linux |
| Video | Network Input | 32 CH IPC input |
| | Network Access Bandwidth | 144Mbps |
| | Network Access Format | 8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps |
| | Output | HDMI × 1:3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 768 |
| Audio | Notwork Input | VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 |
| | Network Input 2-way Audio | 32 CH IPC audio input RCA × 1 |
| | Local Output | RCA×1 |
| Record | Record Stream | |
| | | Dual stream recording |
| | Resolution | 8MP/5MP/4MP/3MP/1080P/960P/720P |
| | Mode | Manual, timer, motion, sensor |
| Playback | Simultaneous Playback | Max 16 CH |
| | Search | Time slice / time / event / tag search |
| | Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| | Function | Play, pause, FF, FB, digital zoom, etc. |
| Alarm | Mode | Manual, sensor, motion, exception |
| | Input | 4 CH local alarm input, 32 CH IPC alarm input |
| | Output | 1CH |
| | Triggering | Record, snap, preset, e-mail, etc. |
| Network | Interface | RJ45 10 / 100 / 1000 Mbps × 1 |
| | PoE Port | RJ45 × 16 |
| | Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP |
| Mobile Device | os | iOS, Andriod |
| Storage | HDD | SATA × 4, max 8T per HDD |
| Backup | Local Backup | U disk, USB mobile HDD |
| | Network Backup | Yes |
| Port | USB | USB 2.0 × 2(one in the front panel and the other in the rear panel) |
| | Remote Controller | Optional |
| Others | Power Supply | ATX |
| | Consumption | ≤ 15W (without HDD) |
| | Dimensions (mm) | 440 × 390 × 70 (W × D × H) |
| | Work Environment | -10 ~ 50 °C , 10% ~ 90% humidity |

Dimensions



Rear Panels

